



Line Prime

1. General Description

Laykold Masters Line Prime is a 100% acrylic, clear drying, emulsion primer that is applied prior to Laykold Masters White Line Paint. The use of the Laykold Masters Line Prime assures crisp, sharp lines and a professional quality finish to the court surface.

Laykold Masters Line Paint is environmentally friendly containing no asbestos, Lead, or Mercury.

Basic Use: Laykold Masters Line Prime is designed to fill the minor voids between the tape and court surface.

2. Safety Guidelines

Always wear the recommended personal protective equipment. Avoid contact with eyes, skin, and clothing.

3. Storage and Packaging

Laykold Masters Line Prime should be kept dry, cool, and in original packaging.

Packaging: 2 gallon unit (2 gallon units are packaged in jugs at 1 gallon each)

4. Coverage

Depending on the surface porosity and texture, the consumption rate is 500-600 feet of 2" line per gallon. One set of tennis court line typically requires 1 gallon of Laykold Masters Line Prime.

Apply Laykold Masters Line Prime undiluted with a paint brush or roller after masking tape is put down. Laykold Masters Line Prime dries with 10 to 15 minutes in good weather conditions. Do not apply masking tape and Laykold Masters Line Prime if rain is imminent. Once Laykold Masters Line Prime is dry, Laykold Masters White Line Paint may be applied. Remove masking tape immediately after playing lines are dry.

Features and Benefits

- ✓ Crisp, sharp lines
- ✓ Professional quality finish
- ✓ Environmentally friendly
- ✓ Contains no asbestos, Lead, or Mercury
- ✓ One component



5. Installation Guidelines

Apply Laykold Masters Line Prime undiluted with a paint brush or roller after masking tape is put down. Laykold Masters Line Prime dries within 10-15 minutes in good weather conditions. Do not apply masking tape and Laykold Masters Line Prime if rain is imminent. Once Laykold Masters Line Prime is dry, Laykold Masters White Line Paint may be applied. Remove masking tape immediately after playing lines are dry.

6. Limitations

- Minimum surface and application temperature: 10°C (50°F)
- Maximum surface and application temperature: 54°C (130°F)
- Do not apply when rain is imminent
- Do not allow to freeze
- Do not dilute
- Completed projects should be allowed a minimum of 48 hours for drying time before releasing for play. CAUTION: acrylic coatings can take 2 to 4 weeks to fully cure depending on weather conditions.

7. Technical Data

Results based on temperature of 23°C (73°F) and 50% Humidity

Flammability	Non-Flammable
Flash Point	None
Color	Milky White, clear when dry

*Based on standard formula calculation

Above figures are guide values and should not be used as a base for specifications

Consult the Safety Data Sheet (SDS) for more details

For complete and latest warranty and product information, please visit www.advpolytech.com





Laykold[®]
MASTERS

Line Prime



ADVANCED POLYMER TECHNOLOGY CORPORATION believes the information herein to be true, accurate and reliable. However, recommendations or suggestions are made without guarantee. Since conditions and disposal are beyond our control, ADVANCED POLYMER TECHNOLOGY CORPORATION disclaims any liability incurred in connection with the use of our products and information contained herein; no warranty, express or implied is given nor is freedom from any patent owned by ADVANCED POLYMER TECHNOLOGY CORPORATION or others to be inferred.

Rev 2 WB 09.13.17